

Glory Online 220V Series 6000VA~10000VA

GO Series Features:

- ✓ Pure Sine Wave Online Double Conversion UPS
- ✓ Multiple Microprocessor Control Technology
- ✓ User Friendly LCD Control Panel
- ✓ Built with IGBT Technology
- ✓ Wide Input Voltage Range
- ✓ Cold Start Function
- ✓ Automatic Self-Test Function
- ✓ True RS-232 Communication Interface
- ✓ SNMP Adapter Slot
- ✓ SNMP Network Management Card (Optional)
- ✓ High Efficient Design to Save More Energy
- ✓ Low Heat Dissipation for Long Time Operation
- ✓ Ensures Total Reliability to Work Under the Worst Operating Conditions
- ✓ Maximize Protection against Lightings, Surges, Disturbances, Blackouts, etc.
- ✓ Redundancy Parallel Feature Included for 6-10K (Optional)
- ✓ Long Time Back Up Models Available (Optional for "L" models)
- ✓ Emergency Power Off (EPO) Available
- ✓ Built-in Isolation Transformer (Optional for "ISO" model)
- ✓ ECO Mode Operation for Energy Saving
- ✓ Maintenance Bypass available for 6K-10K



GLORY ONLINE UPS -6~10K

MODEL		GO-6000	GO-6000L	GO-10000	GO-10000L	GOI-6000L	GOI-10000L
INPUT	Capacity	6000 VA / 4800 W		10000 VA / 8000 W		6000 VA / 4800 W	
	Phase	Single Phase with ground					
	Nominal Voltage	208/220/230/240 VAC					
	Voltage Range	176VAC ~ 300VAC (100% Load)					
	Frequency	46 Hz ~ 54 Hz or 56 Hz ~ 64 Hz					
	Power Factor	≥ 0.99 @ 100% load					
OUTPUT	Voltage Range	208/220/230/240 VAC			104V*2/ 208V or 110V*2/ 220V or 115V*2/ 230V or 120V*2/ 240V		
	Frequency	Line Mode: Same as Input. Battery Mode: 50Hz or 60Hz ±0.1Hz					
	Wave Form	Pure Sinewave					
	Harmonic Distortion	≤ 3% THD (Linear Load) ≤ 5% THD (Non-Linear Load)			≤ 3% THD (Linear Load) ≤ 6% THD (Non-Linear Load)		
	Overload Capacity (Line Mode)	100%~105%:30 mins; 105%~115%:5 mins; >115%: 10 sec					
	Overload Capacity (Battery Mode)	100%~105%:3 min; 105%~115%:30 sec; >115%: 10 sec					
	Auto Retransfer	After Overload Recover 90% Load					
BATTERY	Type	Maintenance Free Sealed Lead-Acid Battery					
	DC Voltage	192V					
	Capacity	12V / 9.0Ah x 16 pcs					
	Standard Model	1A, 2A, 4A, 6A ±10%					
	Long-run Model	1A, 2A, 4A, 6A ±10%					
	Recharger Time	9 hours recover to 90% capacity					
Battery Handle	Fully recharge UPS after complete discharge or every three months when stored						
BYPASS	Automatic	Overload or UPS Failure					
	Transfer Time	0 ms Line Mode to Bypass					
DISPLAY	LCD	UPS status, Load level, Battery level, Input/Output voltage, Discharge timer, and Fault conditions					
AUDIBLE ALARM	Battery Mode	Beep every 4 seconds					
	Battery Low	Beep every second					
	Overload	Beep twice every second					
	Fault	Beep continuously					
OUTPUT	Sockets	Terminal Block					
INTERFACE	Smart RS-232 / USB	Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7, Linux, Unix, and MAC					
	SNMP Card (Optional)	Power management from SNMP manager and web browser					
NETWORK	Surge Protection	Optional					
ENVIRONMENT	Temperature	0 °C ~ 50 °C ; 32 °F ~104 °F					
	Humidity	0-95 % RH Non-condensing					
	Acoustic Noise	Less than 55dBA at 1mt	Less than 58dBA at 1mt	Less than 55dBA at 1mt	Less than 58dBA at 1mt	Less than 55dBA at 1mt	Less than 58dBA at 1mt
NET WEIGHT	W/O Battery (Kgs)	12	16	63	75		
	With Battery (Kgs)	61	66	111	125		
DIMENSIONS	Standard (W x H x D) mm	190*369*688	190*442*688	190*369*700	190*369*700		
	Long (W x H x D) mm	190*369*318	190*442*318	190*369*630	190*442*630		

* Specification Subject to Change without Prior Notice