




Wireless
Charging



Short Circuit
Protection



Multi USB
Optional






Quick
Charging



Quick
Charging

Power Center Wireless Charger Series

MODEL		PCW5U4	PCW4U1Q8	PCW2U1Q1C8
AC INPUT	Input Voltage Range	100~260VAC		
	Frequency	50/60Hz		
WIRELESS CHARGER	Voltage	5V±0.1V		
	Charging Current	500mAh-1000mAh		
	Output Current	5W		
	Charging Efficiency	73%		
	Idle Consumption Power	≤ 50mW		
	Excution Standard	Qi Wireless Charging Standard		
OVER LOAD PROTECTOR	Breaker	ON/Off Switch and Power Safety Shut Down		
ENVIRONMENT	Temperature	0~45°C		
	Acoustic Noise	< 40dB		
	Humidity range	< 90% (non condensed)		
USB CHARGER	Output Current/Watt	4A/20W, Max. Power: 6A/30W	8A/40W	8A/40W
	USB Spec.	TYPE-A*5 (2.4A/port Max.)	TYPE-A*4(2.4A/port Max.) TYPE-A(QC3.0)*1 : 5V 3A/port Max. (3.6V~6.5V/3A ; 6.5V~9V/2A ; 9V~12V/1.5A)	TYPE-A*2(2.4A/port Max.) TYPE-A(QC3.0)*1 : 5V 3A/port Max. TYPE-C(PD)*1 : 5V/3A ; 9V/2A ; 12V/1.5A ; 15V/1.2A
	Port Number	TYPE-A: 1, 2, 3, 4, 5 	TYPE-A: 1, 2, 3, 4, 5 	TYPE-A: 1, 2, 3 TYPE-C: 4 

* Specification Subject to Change without Prior Notice.