

NE Series Features:

- ⚡ Digital with Microprocessor Control
- ⚡ Surge Protector
- ⚡ Voltage Automatic Cutting Protector
- ⚡ Voltage Soft-Start Protection
- ⚡ Preventing High Electrical Spikes
- ⚡ Line RJ-45 /11 Surge Protector (option)
- ⚡ Coaxial Line Surge Protector (option)



Neo Egis Series

MODEL		NE01
DESCRIPTION		Intelligent Voltage Protector
INPUT	Voltage Range	120Vac : 90-140Vac / 220Vac :180-268Vac
	Current	120V:1800W 15A / 220VAC:1540W 7A
	Frequency	50 / 60Hz
	Plug	Nema5-15P / Argentina IRAM
OUTPUT	Voltage	Same as Input
	Frequency	Same as Input
	Outlet	Nema5-15R x1 / Argentina IRAM x1
PROTECTOR	Power Socket Surge Energy Rating	L-N-G ; 14D471K*3pcs 525J
	Power Socket Surge Current	18,000 A
	Delay Time (Slide Switch)	15 seconds / 30 seconds / 180 seconds
	Over High / Low Voltage	Power output Cut-off
	Line RJ-45 /11 Surge Protector (option)	385VDC; Withstanding Surge Current:1200A
	Coaxial Line Surge Protector (option)	Gas Discharge Tube: < 600V, @8/20µs:20KA, @10/1000µs:100A
INDICATOR	Green	Normal Voltage
	Yellow	Over Low Voltage
	Red	Over High Volage
	Switch	ON / OFF / Quick Start
ENVIRONMENT	Humidity	0-95% (Non-condensing)
	Operating Temperature	0°C ~ 40°C
DIMENSIONS	D x W x H (mm)	100 x 49 x 40mm (H Max.60mm)

* Specification Subject to Change without Prior Notice.