

### TCS Series Features:

- ⚡ DC Mini UPS / Auto Start
- ⚡ Manual Select I/P voltage: 5V / 7.5V / 9V / 12V
- ⚡ Universal Adapter
- ⚡ Digital with Microprocessor Control
- ⚡ Battery Level, Battery Life Led Indicator
- ⚡ Over Discharge, Overload, Short Circuit Protection,
- ⚡ Over Charge, Surge Protection
- ⚡ Uses Battery Protection IC
- ⚡ Real Time Back Up
- ⚡ DC Cold Start

### Four Selection Manual Operation



Four Selection Manual Operation

#### Multi-size Connectors (Optional)

M3.5mm X 1.35mm M4.8mm X 1.7mm M5.5mm X 2.5mm



F5.5mm X 2.1mm F5.5mm X 2.1mm F5.5mm X 2.1mm

### Tank Combo Series

MODEL		TCS-2600	TCS-5200
INPUT	Voltage	AC 95 ~ 265 VAC	
	Frequency	50 / 60HZ	
OUTPUT	Voltage	5 / 7.5 / 9 / 12Vdc $\pm$ 5% Selected by Switch	
	Power rating	12W	
	Ripple	150mV	
BATTERY	Type	Lithium-Ion 18650 Type Battery	
	Voltage	3.7V	
	Capacity	2600mAh x1pc	5200mAh (1P) (2600mAh*2pcs)
	Backup Time	Half Load 60mins Full Load 30mins	Half Load 120mins Full Load 55mins
PROTECTION	Input	Fuse for Overload & Short Circuit Protection	
	Output	MCU for Over Discharge, Overload, Short Circuit Protection	
	Battery	Battery Protection IC for Over Charge, Over Discharge, Overload, Short Circuit Protection	
INDICATORS	LED	Power On x1, Battery Mode x 1, Charging x 1, Battery Life x 1	
	Input Cord	AC Power Cable	
CORD	Output Cord	DC Power cord : Jack 5.5mm x 2.1mm 20Awg	
ACCESSORY	Connector (=3pcs)	M5.5mm x 2.5mm / M4.8mm x 1.7mm / M3.5mm x 1.35mm	
	Operation Temperature	0°C - 40°C	
ENVIRONMENT	Humidity	0% - 95% Non-condensing	
DIMENSION	D x W x H(mm)	153 x 70 x 33mm	
WEIGHT	Gram	250g	290g
CASE	ABS 94V0	Black	

\* Specification Subject to Change without Prior Notice.