

OS Series Features:

- ⚡ DC On-line UPS / Auto Start
- ⚡ Intelligent Auto-Select Voltage: 12V / 15V / 19V / 24V
- ⚡ Digital with Microprocessor Control
- ⚡ Led Indicator
- ⚡ Over Discharge, Overload, Short Circuit Protection, Over Charge, Surge Protection
- ⚡ Uses Battery Protection IC
- ⚡ Real Time Backup

Auto Detect Voltage



Output Terminal

Multi-size Connectors (Optional)



Omni Supply Series (OS24 & OS36)

MODEL		OS24-5200	OS36-10400
INPUT	Voltage	12V ~24VDC	
	Frequency	50 / 60HZ	
OUTPUT	Voltage	12V / 15V / 19V / 24V Auto-Selection	
	Current	24W	36W
BATTERY	Type	Lithium-Ion 18650 Type Battery	
	Voltage	7.4V	
	Capacity	2600mAh (1S)(2600mAh*2pcs)	5200mAh (2S2P)(2600mAh*4pcs)
	Backup Time	Half Load 50mins / Full Load 20mins	
PROTECTION	Input	Fuse for Overload & Short Circuit Protection	
	Output	MCU for Over Discharge, Overload, Short Circuit Protection	
	Battery	Battery Protection IC for Over Charge, Over Discharge, Overload, Short Circuit Protection	
INDICATORS	LED	Power On x 1, Function Alarm x 1, Battery Mode x 1, Charging x 1	
CORD	Input Cord	Terminal	
	Output	Terminals*1 & DC Power cord : Jack 5.5mm x 2.1mm 20Awg ; L:300 mm	
ACCESSORY	Connector (=6pcs)	F5.5mm x 2.5mm / M5.5mm x 2.1mm & F5.5x2.1mm / M5.5x2.5mm	
		F4.8mm x 1.7mm / M5.5mm x 2.1mm & F5.5x2.1mm / M4.8x1.7mm	
DIMENSION	D x W x H(mm)	105mm x 80mm x 43mm	
CASE	ABS 94V0	230g	320g
		Black	

* Specification Subject to Change without Prior Notice.