

OS Series Features:

- ⚡ DC UPS / Auto Start
- ⚡ Intelligent Auto-Select Voltage: 5V / 7.5V / 9V / 12V
- ⚡ Digital with Microprocessor Control
- ⚡ Led Indicator
- ⚡ Over Discharge, Overload, Short Circuit Protection, Over Charge, Surge Protection
- ⚡ Uses Battery Protection IC
- ⚡ Real Time Backup

Auto Detect Voltage



OS12-2600 / OS12-5200



OS24E9-4000 / OS24E12-4000

Multi-size Connectors (Optional)



Omni Supply Series (OS12 / OS24E)

MODEL		OS12-2600	OS12-5200	OS24E9-4000 / OS24E12-4000
INPUT	Voltage	5V ~12V DC		
	Current	5V / 7.5V/ 9V/ 12V Auto-Selection		
OUTPUT	Voltage	9V or 12V Single Voltage		
	Current	9V: 24W 2.7A / 12V: 24W 2A		
BATTERY	Current	Lithium-Ion 18650 Type Battery		
	Type	3.7V		
	Voltage	7.4V		
	Quantity	2600mAh / 9.62Wh	5200mAh / 19.24Wh (1P)	2000mAh / 14.8Wh (1S)
	Backup Time	2600mAh x1pc	2600mAh x2pcs	2000mAh x2pcs
PROTECTION	Input	Half Load 70mins Full Load 35mins(15mins)		
	Output	Over- Voltage, Over-load & Short Circuit Protection		Half Load 120mins Full Load 55mins
	Battery	MCU for Over- Charge, Over- Discharge, Over-Load, Short Circuit Protection		
INDICATORS	LED	Power On x 1, Function Alarm x 1, Battery Mode x 1, Charging x 1, Voltage indication x 1		
	Output Cord	DC Power cord : Jack 5.5mm x 2.1mm 20Awg ; L:300mm		
ACCESSORY	Connector (=6pcs)	Power On x 1, Battery Mode x 1		
	D x W x H(mm)	85 x 57 x 42mm		
WEIGHT	Gram	110g	162g	160g
CASE	ABS 94V0	Black		

* Specification Subject to Change without Prior Notice.